

**MATERIAL SAFETY DATA SHEET**

LP659D POLAR WHITE 4.3 VOC

Page:

**PRODUCT NAME: LP659D POLAR WHITE 4.3 VOC**  
**PRODUCT CODE: LP659**

**HMIS CODES: H F R P**  
**2 3 0 X**

=====**SECTION I - MANUFACTURER IDENTIFICATION**=====

**MANUFACTURER'S NAME: RILEY PAINT COMPANY**  
**ADDRESS : 860 WASHINGTON**  
**BURLINGTON, IOWA 52601**

**EMERGENCY PHONE : 1-800-424-9300**    **DATE PREPARED : 5-27-2011**  
**INFORMATION PHONE : 319-753-0105**    **NAME OF PREPARER : Riley Paint Company**

=====**SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION**=====

<b>REPORTABLE COMPONENTS</b>	<b>CAS NUMBER</b>	<b>VAPOR PRESSURE MM HG @ TEMP</b>		<b>WEIGHT PERCENT</b>
* XYLENE/DIMETHYLBENZENE OSHA PEL/TWA: 100, ACGIH TLV/STEL: 150, OSHA/STEL: 150 STEL, ACGIH TLV/TWA: 100	1330-20-7	7.00000	68.00000	24
TITANIUM DIOXIDE PIGMENT OSHA PEL: 10mg/m3, ACGIH TLV: 10mg/m3, OTHER: 10mg/m3	13463-67-7	0.00000	0.00000	21
ACETONE/DIMETHYLKETONE/2-PROPANONE OSHA PEL: 750 PPM, ACGIH TLV: 750 PPM	67-64-1	186.0000	68.00000	7
* PHENYLETHANE/ETHYL BENZENE OSHA PEL/TWA: 100PPM, ACGIH TLV/TWA: 100PPM, ACGIH TLV/STEL: 125 OSHA PEL/STEL: 125PPM	100-41-4	3.66000	68.00000	6
* TOLUENE/METHYL BENZENE OSHA PEL: 200, ACGIH TLV: 100	108-88-3	22.00000	68.00000	5
AROMATIC 100 HYDROCARBON SOLVENT ACGIH TLV: 25 PPM; OTHER: 50 PPM STEL	64742-95-6	4.4	68	3
AROMATIC 150 HYDROCARBON SOLVENT ACGIH TLV: 25 PPM; OSHA PEL: 25 PPM STEL	64742-94-5	1.00000	68.00000	2
* 1,2,4 TRIMETHYL BENZENE OSHA PEL: 25 PPM, ACGIH TLV: 25 PPM	95-63-6	1.70000	68.00000	1

\* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

=====**SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS**=====

**BOILING RANGE: 132 DEG F - 350 deg F**    **SPECIFIC GRAVITY (H2O=1): 1.14**  
**VAPOR DENSITY: HEAVIER THAN AIR**    **EVAPORATION RATE: SLOWER THAN ETHER**  
**MATERIAL V.O.C.: 3.99 lb/gl**    **SOLUBILITY IN WATER: insoluble**  
**APPEARANCE AND ODOR: Liquid coating/solvent odors**

=====**SECTION IV - FIRE AND EXPLOSION HAZARD DATA**=====

**FLASH POINT: 12 DEG F**    **METHOD USED: TCC**  
**FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 0.90000**    **UPPER: 12.6**

**EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL**

**SPECIAL FIREFIGHTING PROCEDURES**

Full protective equipment including self-contained breathing apparatus should be used. RED LABEL - FLAMMABLE LIQUID

**UNUSUAL FIRE AND EXPLOSION HAZARDS**

Should be stored in tightly closed containers away from heat, electrical equipment, sparks and open flame.

=====**SECTION V - REACTIVITY DATA**=====

**MATERIAL SAFETY DATA SHEET**

LP659D POLAR WHITE 4.3 VOC

Page:

**STABILITY: STABLE**

**CONDITIONS TO AVOID**

Elevated temperatures and open containers.

**INCOMPATIBILITY (MATERIALS TO AVOID)**

Avoid strong oxidizing materials

**HAZARDOUS DECOMPOSITION OR BYPRODUCTS**

May produce hazardous fumes when heated to decomposition as in welding. Fumes may contain carbon monoxide.

**HAZARDOUS POLYMERIZATION: WILL NOT OCCUR**

===== **SECTION VI - HEALTH HAZARD DATA** =====

**INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Anesthetic irritation of the respiratory tract or acute nervous system depression characterized by dizziness, staggering and confusion.

**SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Severe irritant, redness, tearing and blurred vision. Prolonged or repeated exposure can cause moderate irritation, defatting and dermatitis.

**SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

PENETRATES SKIN READILY. FREQUENT OR WIDESPREAD CONTACT MAY RESULT IN ABSORPTION OF POTENTIALLY HARMFUL AMOUNTS WHICH CAN CAUSE DAMAGE TO KIDNEYS, LIVER, BLOOD AND/OR BONE MARROW.

**INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Can cause gastrointestinal irritation, nausea, vomiting, and diarrhea. Aspiration of material into lungs can cause chemical pneumonitis which can be fatal.

**HEALTH HAZARDS (ACUTE AND CHRONIC)**

Acute-Anesthetic irritation of the respiratory tract or acute nervous system depression characterized by headache, dizziness, staggering, confusion. Skin or eye contact: Primary irritant. Chronic-Extensive and continued over exposure may result in respiratory or skin sensitivity.

**CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED: Yes**

WHEN HANDLED PROPERLY, NO ACUTE OR LONG TERM HAZARD IS EXPECTED

**MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE**

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure to this product.

**EMERGENCY AND FIRST AID PROCEDURES**

Remove to fresh air. Wash skin contact area with soap and water. Flush eyes with water and report to a physician immediately.

===== **SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE** =====

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

Remove all sources of ignition. Avoid breathing vapors. Ventilate area. Contain and remove with inert absorbent and nonsparking tools.

**MATERIAL SAFETY DATA SHEET**

LP659D POLAR WHITE 4.3 VOC

Page:

**WASTE DISPOSAL METHOD**

Dispose in accordance with local, state and federal regulations. Incinerate in approved facility. Do not incinerate closed containers.

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING**

Contains Solvent. Keep away from heat, sparks, open flames. Use with adequate ventilation. Avoid prolonged or repeated breathing of vapors. Avoid prolonged or repeated skin contact. Do not leave containers open.

**OTHER PRECAUTIONS**

Do not take internally. Avoid prolonged contact with skin, ground all containers when pouring. Keep away from open flames.

===== **SECTION VIII - CONTROL MEASURES** =====

**RESPIRATORY PROTECTION**

In restricted areas, use approved chemical mechanical filters to remove gas and vapors. In a confined area, use approved airline type respirators or hoods.

**VENTILATION**

Local exhaust is preferable; however, general mechanical is acceptable. Sufficient ventilation, in volume and pattern, should be provided to keep the vapor concentration below applicable OSHA requirements.

**PROTECTIVE GLOVES**

Use neoprene gloves to prevent skin contact.

**EYE PROTECTION**

Use chemical goggles.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT**

Safety showers and eyewash fountains

**WORK/HYGIENIC PRACTICES**

Wash hands before eating or using washroom. Smoke in smoking areas only.

===== **SECTION IX - TRANSPORTATION INFORMATION** =====

PAINT,3,UN1263,PG II RED LABEL - FLAMMABLE LIQUID

===== **SECTION X - DISCLAIMER** =====

The information in this MSDS and environmental data sheet was obtained from sources which we believe are reliable. However, the information is provided without any representation or warranty, expressed or implied, regarding its accuracy or completeness.